

- Electronic and Electricity
- Industry Electricity
- Environment Monitoring
- Ranging and Mapping
- Basic Education

Your location : Home >



Mini Clamp Meters UT210D

UT210 series Mini Clamp Meters with the characteristics of high reliability, high security, automatic measurement range and miniaturization, which can accurately measure current signal; Product chip set up VFC start-up mode, the inside will pass through a specific filter circuit, filter the high frequency interference signal to ensure the accuracy of the measurement data. It is suitable for frequency conversion voltage, current with VFC, full range overload protection and unique appearance design, which becomes more superior performance of electrical instruments. It is suitable for school, smelt, communication, manufacturing, petroleum, national defense, electric power, chemical industry etc. It's an ideal tool for the maintenance and repair of the circuit, power equipment.



[Download Photo](#)



[Product description](#)
[Technical Specifications](#)
[Models & Comparison](#)
[Accessories](#)
[Download Manual](#)

Specifications	Range	Best Accuracy
Model		UT210D
AC Current (A)	20A/200A	±(2.5%+8)
DC Current (A)	20A/200A	±(2%+3)
AC Voltage (V)	2V/20V/200V/600V	±(1%+3)
DC Voltage (V)	200mV/2V /20V/200V/600V	±(0.7%+3)
Resistance (Ω)	200Ω/2kΩ/20kΩ/200kΩ /2MΩ/20MΩ	±(1.0%+2)
Frequency (Hz)	10Hz/100Hz /1kHz/10kHz/60kHz	±(0.1%+4)
Capacitance (F)	20nF/200nF/2μF/20μF /200μF/2mF/20mF	±(4%+5)

Temperature (°C)	-40°C ~ 1000°C	±(1%+3)
Temperature (°F)	-40°F ~ 1832°F	±(1.5%+5)
Features		
Display Count		2000
Jaw Capacity		Around 17mm
Auto Range		√
True RMS		√
Diode		√
Data Hold		√
MIN/MAX		
Continuity Buzzer		√
Data Storage		
LCD Backlight		√
Auto Power Off	Around 15 minutes	√
Low Battery Indication	≤2.5V	√
Input Protection		√
Input Impedance for DCV	> 10MΩ	√
Zero		√
NCV		√
General Characteristics		
Power	AAA 1.5V × 2	
LCD Size	39.3mm × 26.5mm	
Product Color	Red+Grey	
Product Net Weight	170g	
Product Size	175mm × 60mm × 33.5mm	
Standard Accessories	Batteries, Test Lead, Point Contact Temperature Probe	
Standard Individual Packing	Gift Box, Carrying Bag, English Manual	
Standard Quantity Per Carton	40PCs	
Standard Carton Measurement	385mm × 345mm × 305mm	
Standard Carton Gross Weight	11kg	

Related products

Not add content...